


**RT-3**  
**Polyolefin, Semi - Rigid,**  
**Heat - Shrinkable Tubing**



**Table 1: Dimensions** (inches)

Size	As Supplied	Recovered	
	Inside Diameter (D)	Inside Diameter Maximum (d)	Wall Thickness Nominal (W)
No.1	.240 ± .015	.095	.031
No.2	.320 ± .015	.125	.031
No.3	.375 ± .020	.150	.031
No.4	.485 ± .020	.200	.031

**Longitudinal Change:** +0 to -10%

**Material:** The tubing shall be fabricated from thermally stabilized, flame resistant, modified polyolefin and shall be cross linked by irradiation. It shall be homogeneous and essentially free from flaws, defects, pinholes, bubbles, seams, cracks and inclusions.

**Properties::** Except as specified above, the finished tubing shall meet all the requirement of Raychem specification RT-360.

**Specification Control Drawing**

	TE Connectivity 300 Constitutional Drive Menlo Park, CA 94025 USA		<b>Raychem</b>	Title: <b>RT-3</b> <b>Polyolefin, Semi - Rigid</b> <b>Heat - Shrinkable Tubing</b>		
	TE Connectivity reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application			Document No : <b>RT-3</b>		
Cage Code: 06090	Scale: None	Size: A	Rev. Date: 16-Apr-11	Rev.: B1	Sheet: 1 of 1	