

Product: [1317SB](#) 



Shipboard Speaker, 4 conductor 12 AWG TC, CMG-LS

Product Description

Shipboard Speaker, 4 conductor 12 AWG stranded tinned copper conductors, polypropylene insulation, LSZH jacket with ripcord.

Technical Specifications

Product Overview

Suitable Applications:	Speaker, Audio, Control, Intercom, ABS Type Approved, Shipboard, CMG-LS, IEEE 45 clause 23, IEC 60092-376 clause 17, 60092-351, 60754-1, 60754-2, 61034, UL1685 FT4 Loading, Limited Smoke, IEC 60332-3-22 (Category A), 60332-1, IEEE 1202
------------------------	---

Physical Characteristics (Overall)

Conductor				
AWG	Stranding	Material	Nominal Diameter	No. of Conductors
12	65x30	TC - Tinned Copper	0.087 in	4
Conductor Count:		4		

Insulation		
Material	Nominal Diameter	Nominal Wall Thickness
PP - Polypropylene	0.115 in	0.011 in

Color Chart	
Number	Color
1	Black
2	White
3	Red
4	Green

Inner Shield Material

Type
Unshielded

Outer Shield Material

Type
Unshielded

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
LSZH - Low Smoke Zero Halogen flame retardant	0.382 in	0.052 in

Electrical Characteristics

Conductor DCR		
Nominal Conductor DCR	Nominal Conductor DCR	Conductor Resistance
1.56 Ohm/1000ft	1.56 Ohm/1000ft	

Capacitance

Nom. Capacitance Conductor to Conductor

32 pF/ft

Inductance

Nominal Inductance
0.16 µH/ft

Current

Max. Recommended Current [A]
21 Amps per Conductor at 25°C

Voltage

UL Voltage Rating
300 V RMS

Temperature Range

UL Temp Rating:	105°C
Operating Temp Range:	-30°C To +105°C

Mechanical Characteristics

Bulk Cable Weight:	124 lbs/1000ft
Max. Pull Tension:	338 lbs
Min Bend Radius/Minor Axis:	4 in

Standards

NEC/(UL) Compliance:	CMG-LS
CEC/C(UL) Compliance:	CMG-LS
CPR Euroclass:	Fca
IEEE Compliance:	Std. 45 clause 23
Other Compliance:	UL444, ABS Type Approval Certificate 06-HS184641E

Applicable Environmental and Other Programs

Environmental Space:	Indoor/Outdoor
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	Yes
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-08-07
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading, Limited Smoke
CSA Flammability:	FT4
IEC Flammability:	60332-1^60332-3-22 (Category A)
IEEE Flammability:	1202
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

--

Variants

Item #	Color	Putup Type	Length	UPC
1317SB 0101000	Black	Reel	1,000 ft	612825111801

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

History

Update and Revision:	Revision Number: 0.229 Revision Date: 06-08-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.