

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

## NOTES:

1. SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS AND TO INDICATE PACKAGE QUANTITY.
2. 110 CONNECTORS ON BOTH ENDS. THE PATCH CORDS CAN BE USED WITH PAN-PUNCH™ 110 CONNECTING BLOCKS.
3. FEATURES INCLUDE A CLEAR CAP TO ENSURE PROPER WIRE SEQUENCE AND CONNECTOR ORIENTATION. RETAINING CLIPS SECURE THE JACKET CLOSE TO THE POINT OF TERMINATION WHICH MINIMIZES WIRE UNTWISTING. INTEGRAL STRAIN RELIEF MINIMIZES STRESS ON WIRES DURING DISCONNECTION.
4. POLARIZED TO PREVENT REVERSE INSTALLATION TO CONNECTOR BLOCK.
5. CATEGORY 3 UNSHIELDED TWISTED PAIR CABLE WITH 24AWG STRANDED TINNED COPPER CONDUCTOR.
6. DIMENSIONS IN PARENTHESES ARE IN METRIC.

| CONTACT | CABLE WIRE COLOR |
|---------|------------------|
| 1       | WHITE/BUE        |
| 2       | BLUE             |

IDENTIFICATION LABEL

TWIST TIE

.29  
[7.3]

2.02  
[51.3]

.35  
[8.8]

CONTACT 1

| PANDUIT P/N    | MIN. CABLE LENGTH | WEIGHT                             |
|----------------|-------------------|------------------------------------|
| P110PC11G2Y    | 2 FT.             | .24 LB/10 PCS<br>(112.1 g/10 PCS)  |
| P110PC11G3Y    | 3 FT.             | .31 LB/10 PCS<br>(144.5 g/10 PCS)  |
| P110PC11G4Y    | 4 FT.             | .38 LB/10 PCS<br>(176.9 g/10 PCS)  |
| P110PC11G5Y    | 5 FT.             | .45 LB/10 PCS<br>(209.3 g/10 PCS)  |
| P110PC11G6Y    | 6 FT.             | .52 LB/10 PCS<br>(241.7 g/10 PCS)  |
| P110PC11G7Y    | 7 FT.             | .59 LB/10 PCS<br>(274.1 g/10 PCS)  |
| P110PC11G8Y    | 8 FT.             | .66 LB/10 PCS<br>(306.5 g/10 PCS)  |
| P110PC11G9Y    | 9 FT.             | .73 LB/10 PCS<br>(338.9 g/10 PCS)  |
| P110PC11G12Y   | 12 FT.            | 1.93 LB/10 PCS<br>(436.1 g/10 PCS) |
| P110PC11G15Y   | 15 FT.            | 1.15 LB/10 PCS<br>(533.3 g/10 PCS) |
| P110PC11G18Y   | 18 FT.            | 1.36 LB/10 PCS<br>(630.5 g/10 PCS) |
| P110PC11G.5MY  | .5M               | .22 LB/10 PCS<br>(100.45g/10 PCS)  |
| P110PC11G1MY   | 1M                | .33 LB/10 PCS<br>(153.6 g/10 PCS)  |
| P110PC11G1.5MY | 1.5M              | .45 LB/10 PCS<br>(206.8 g/10 PCS)  |
| P110PC11G2MY   | 2M                | .56 LB/10 PCS<br>(259.9 g/10 PCS)  |
| P110PC11G3MY   | 3M                | .79 LB/10 PCS<br>(366.2 g/10 PCS)  |
| P110PC11G4MY   | 4M                | 1.02 LB/10 PCS<br>(472.5 g/10 PCS) |
| P110PC11G5MY   | 5M                | 1.25 LB/10 PCS<br>(578.8 g/10 PCS) |
| P110PC11G6MY   | 6M                | 1.48 LB/10 PCS<br>(685.1 g/10 PCS) |

PART NUMBER

P110PC1\*\*\*Y

TITLE

CATEGORY 3 110 PATCH CORD

CUSTOMER DRAWING

ITEM REVISION NAME

M02479JQ/05


DATASET FILE NAME

M02479JQ\_DC253/00B

UNLESS OTHERWISE SPECIFIED,  
DIMENSIONAL TOLERANCES ARE: IN [ mm ]

.X ±  
.XX ± .03 [ .8 ]

.XXX ± .010 [ .3 ]  
ANGLES ±

THIRD ANGLE  
PROJECTION

MATERIAL:

DRAWING NUMBER:

02479-253

DRAWN BY

DATE

CHK

SCALE

NER

3-17-06

WJC

NONE

SHT 1 OF 1

SIZE

A

| REV | DATE    | BY  | CHK  | APR | DESCRIPTION                     | ECN       |
|-----|---------|-----|------|-----|---------------------------------|-----------|
| 1   | 5/28/14 | JSP | REFR | MMR | A. REVISED DRAWING TITLE BLOCK. | 02479-253 |
| R   | 3-17-06 | NER | WJC  | RMD | RELEASED TO PRODUCTION          | 02479-253 |