

4

3

2

1

THIS DRAWING IS UNPUBLISHED

RELEASED FOR PUBLICATION

2017

© COPYRIGHT 1987

BY TE CONNECTIVITY

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	REVISED PER PCN E-17-016249	03NOV2017	JA	DM

1.030±.015  
[26.16±.38]

INSPECTION HOLE

.225±.005  
[5.70±.12]

.052±.005  
[1.32±.12]

.470±.010  
[11.94±.25]

∅ .422±.005  
[10.71±.12]

∅ .234±.005  
[5.94±.12]

∅ .345±.005  
[8.76±.12]

3. FOR CONTACT PERFORMANCE AND APPLICATION CHARACTERISTICS SEE DRAWING 0425-015-0000.

2. THIS CONTACT MAY BE CRIMPED WITH HDP-400 POWER CRIMPER OR HDT-04-08 HAND TOOL. SEE DRAWING 0425-205-0000 FOR APPLICABLE WIRE SIZE AND CRIMP INFORMATION.

1. WHEN XX = 90 OR 141: PLATING IS NICKEL.

NOTES: UNLESS OTHERWISE SPECIFIED

TE INTERNAL PN	DEUTSCH PN
0460-204-0490	0460-204-04141

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN D. MEYER 29NOV2000	TE Connectivity	
DIMENSIONS: INCHES [mm]		CHK B. BYFORD 18DEC2000		
		APVD R. REED 19DEC2000	NAME CONTACT PIN SIZE 4	
		PRODUCT SPEC 0425-015-0000	SIZE A3	CAGE CODE 4AFU8
MATERIAL		APPLICATION SPEC 0425-205-0000	RESTRICTED TO	
FINISH		WEIGHT 8.33g	SCALE 6:1	SHEET 1 OF 1
		CUSTOMER DRAWING	REV A1	

1470-19 (3/13)