

Material

- | | | | |
|-----|-----------------|-------|------|
| ⚠ | Electrical: | cULus | CQC |
| ⚠ ● | Voltage rating: | 300V | 300V |
| ● | Current rating: | 2A | 2A |

-

 Safety Approval:

△ HC xx B 2 x 0 xxxx G

No. OF POLES

02: 2 POLES

24: 24 POLES

COLOR

2: Red

3: Orange

5: Green (RAL 6018/T)

8: Grey (RAL 7004/P)

0000: "@" Logo (Standard)

000A: "ANYTEK" Mark

Any special item by
customer request.
please contact sales
department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	HC 2.5mm -High profile Series						
PART NO.	HCxxB2x0xxxxG			DWG NO.	8HC0501		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance
		Runner 2010.12.25	Tony 2008.09.16			UNIT: mm	X. ±0.50
				SHEET: 01/01		SCALE: NONE	X.X ±0.30
						REV: E	X.XX ±0.10
							X° ±1°