Product datasheet Characteristics

9007AW12M16

Body type	Standard
Device short name	AW
Series name	Heavy duty

Complementary

Line Rated Current	15 A
Body material	Cast zinc
Contact operation	Snap action
Fluid connection type	0.5 inch BSP conduit entrance
Maximum displacement angle	30°
Switch actuation	CCW
Tilting angle	5°
Torque value	2.75 lbf.in
Tripping angle	2.5 °

Environment

ambient air temperature for operation	-60185 °F	
NEMA degree of protection	NEMA 1/2/4/12/13	
product certifications	CE CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR	_

Offer Sustainability

Not Green Premium product	Not Green Premium product	
Will not be Compliant	Will not be Compliant	
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold	
Available	Available	
Need no specific recycling operations	Need no specific recycling operations	
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Diisononyl phthalate (DINP), which is known to the State Diisononyl phthalate (DINP), which is known to the State of California to cause of California to cause cancer, and		
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth		

Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months