

## Silicon Power Schottky Diode


$V_{RRM} = 150\text{ V} - 200\text{ V}$

$I_{F(AV)} = 240\text{ A}$

### Features

- High Surge Capability
- Types from 150 V to 200 V  $V_{RRM}$
- Not ESD Sensitive

D-67 Package



Maximum ratings, at  $T_j = 25\text{ °C}$ , unless otherwise specified ("R" devices have leads reversed)

| Parameter                       | Symbol    | Conditions | MBRH240150(R) | MBRH240200(R) | Unit |
|---------------------------------|-----------|------------|---------------|---------------|------|
| Repetitive peak reverse voltage | $V_{RRM}$ |            | 150           | 200           | V    |
| RMS reverse voltage             | $V_{RMS}$ |            | 106           | 141           | V    |
| DC blocking voltage             | $V_{DC}$  |            | 150           | 150           | V    |
| Operating temperature           | $T_j$     |            | -55 to 150    | -55 to 150    | °C   |
| Storage temperature             | $T_{stg}$ |            | -55 to 150    | -55 to 150    | °C   |

Electrical characteristics, at  $T_j = 25\text{ °C}$ , unless otherwise specified

| Parameter                                                          | Symbol      | Conditions                                     | MBRH240150(R) | MBRH240200(R) | Unit |
|--------------------------------------------------------------------|-------------|------------------------------------------------|---------------|---------------|------|
| Average forward current (per pkg)                                  | $I_{F(AV)}$ | $T_C = 125\text{ °C}$                          | 240           | 240           | A    |
| Peak forward surge current                                         | $I_{FSM}$   | $t_p = 8.3\text{ ms}$ , half sine              | 3300          | 3300          | A    |
| Maximum instantaneous forward voltage                              | $V_F$       | $I_{FM} = 240\text{ A}$ , $T_j = 25\text{ °C}$ | 0.88          | 0.92          | V    |
| Maximum instantaneous reverse current at rated DC blocking voltage | $I_R$       | $T_j = 25\text{ °C}$                           | 1             | 1             | mA   |
|                                                                    |             | $T_j = 100\text{ °C}$                          | 10            | 10            |      |
|                                                                    |             | $T_j = 150\text{ °C}$                          | 50            | 50            |      |

### Thermal characteristics

|                                   |                 |  |      |      |      |
|-----------------------------------|-----------------|--|------|------|------|
| Thermal resistance, junction-case | $R_{\theta JC}$ |  | 0.30 | 0.30 | °C/W |
|-----------------------------------|-----------------|--|------|------|------|

Figure .1- Typical Forward Characteristics




Figure .2- Forward Derating Curve




Figure.3-Peak Forward Surge Current








Figure .4- Typical Reverse Characteristics




## Package dimensions and terminal configuration

Product is marked with part number and terminal configuration.



Baseplate  
Common Cathode



Baseplate  
R=Common Anode

| DIMENSIONS |             |       |       |       |      |
|------------|-------------|-------|-------|-------|------|
| DIM        | INCHES      |       | MM    |       | NOTE |
|            | MIN         | MAX   | MIN   | MAX   |      |
| A          | 1.515       | 1.560 | 38.48 | 39.62 |      |
| B          | .725        | .775  | 18.42 | 19.69 |      |
| C          | .595        | .625  | 15.11 | 15.88 |      |
| D          | 1.182       | 1.192 | 30.02 | 30.28 |      |
| E          | .736        | .744  | 18.70 | 18.90 |      |
| F          | .152        | .160  | 3.86  | 4.061 | Ø    |
| G          | 1/4- 20 UNC |       |       |       |      |
| H          | .540        | .580  | 13.72 | 14.73 |      |
| J          | .156        | .160  | 3.96  | 4.06  |      |
| K          | .480        | .492  | 12.20 | 12.50 | Ø    |
| L          | .120        | .130  | 3.05  | 3.30  |      |

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[GeneSiC Semiconductor:](#)

[MBRH240150R](#)