


JKL LAMP PART NO.	COLOR LCD HIGH OUTPUT WHITE 8800°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) AVERAGE
BF3294-24B	x = .285 y = .278	1550	620	5 ± 1	28,000 ± 10%	40,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<b>METRIC</b>  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>			
					TITLE		MINIATURE COLD CATHODE FLUORESCENT LAMP			
A			ELECTRICAL SPEC CHANGES		8/5/04		DRAWN BY		L. WENGSTROM	
			RELEASE & CANCEL P-0308-05		5/17/04		APPV'D BY		J.K. 8/5/04	
REV. NO.			DESCRIPTION/ECO NUMBER		APPV'D DATE		- CAD DRAWING -		MANUAL REVISIONS NOT PERMITTED	
							SIZE		A	
							FSCM NO.		55335	
							DRAWING NO.		BF3294-24B	
							SCALE		NONE	
							RELEASED DATE		5/17/04	
							REVISION DATE		8/5/04	
							REV. NO.		A	
							SHEET		1 OF 1	