## **KAXZ1S191**



#### Main

Range of product	Harmony Series K	
Product or component type	Cam switch operating head	
Component name	KAX	
Product compatibility	Front mounting bodies 12 and 20 A by Ø 22 mm hole	
Cam switch head type	With bezel Ø 28.5 mm, metal	
Type of operator	Key Ronis 455	
Rotary handle padlocking	Without	
Presentation of legend	With mat black legend	
Switching angle	90 °	

### Complementary

Mechanical durability	1000000 cycles
CAD overall width	1.14 in (29 mm)
CAD overall height	1.14 in (29 mm)
CAD overall depth	0.83 in (21 mm)
Product weight	0.14 lb(US) (0.065 kg)

#### **Environment**

protective treatment	TC	
ambient air temperature for operation	-13131 °F (-2555 °C)	•
ambient air temperature for storage	-40158 °F (-4070 °C)	
shock resistance	30 gn conforming to IEC 68-2-27	
vibration resistance	5 gn, 10150 Hz conforming to IEC 68-2-6	
IP degree of protection	IP65 conforming to IEC 529 IP65 conforming to NF C 20-010	

## Offer Sustainability


WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Nickel compounds, which is known to the State of California to cause cancer, and	Nickel compounds, which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Star of California to cause birth defects or other reproductive harm.	teDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

# Contractual warranty

•		
Warranty period	18 months	

### **Operating Head**

For Ø 22 mm/0.87 in. Hole, Front Mounting Body



## **Operating Head**

### Panel Cut-out

mm in.

