

Cable gland - G-INS-PG48-L68N-NNES-S - 1411181

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 34 mm ... 44 mm, Shielding: No, Connecting thread: Pg48, Color: silver

Product Features



Key commercial data

Packing unit	1 pc
Custom tariff number	74199990
Country of origin	Turkey

Technical data

Dimensions

Length	63.4 mm
Length without connecting thread	49.4 mm
Connecting thread diameter	59.3 mm
Wrench size, union nut	64 mm
Wrench size, support	64 mm
Hexagon angular dimension GRP	70 mm
Length of the connecting thread	14 mm
External cable diameter	34 mm ... 44 mm

Ambient conditions

Degree of protection	IP68 (5 bar, 30 min.)
Ambient temperature (operation)	-40 °C ... 100 °C

General

Cable gland material	Brass, nickel-plated
Cable seal material	CR

Cable gland - G-INS-PG48-L68N-NNES-S - 1411181

Technical data

General

O-ring material	NBR
Shielded	No
Thread type on connection side	Pg48
Torque	40 Nm ... 50 Nm (Union nut)
Color	silver

Classifications

eCl@ss

eCl@ss 5.1	27081002
eCl@ss 6.0	27081002
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals


Approvals

UL Listed

Ex Approvals

Approvals submitted

Approval details

UL Listed 

Drawings

Cable gland - G-INS-PG48-L68N-NNES-S - 1411181

Dimensional drawing

